Two Glass Swing Door BackBar

Range: BackBar
SKOPE ID: BB002
Dimensions: 1480 mm (W) × 590 mm (D) × 1025 mm (H)*
Capacity: 410 L

* Height with castors is adjustable from 1015 to 1035.

Project:

Item #:



A glass door under-bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The 'frameless' glass doors provide maximum product viewing and are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. For high humidity tropical environments heated glass versions are available. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



2 YEAR
Warranty

Natural Refrigerant


GEMS

SKOPE-connect

© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.

Email: skope@skope.com AUS Freephone: 1800 121 535 NZ Freephone: 0800 947 5673 skope.com

BB.2.GSW



Cabinet

Type	BackBar	
Finish	Powdercoat galvanised steel or stainless steel	
Insulation	Type	PU foam
	Thickness (mm)	50
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)
Doors	Type	Glass swing door (double-glazed, low-e, argon-filled)
	Opening Size	Height (mm) 730
		Width (mm) 460
Shelving	Four adjustable height powder-coated wire shelves 4 × outer shelf (497W × 440D)	
Lighting*	1 × 16 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling	

Dimensions†

	External	Internal	Packed
Width (mm)	1480	1020	TBC
Depth (mm)	590	530	TBC
Height (mm)	**1015 to 1035 (standard castors)** 920 (plinth mount)	758	TBC
Weight (kg)	180		TBC
Capacity (L)	410		
Footprint (m^2)	0.87		

Ventilation (mm)

Top	Not required	**Sides**	Not required	**Rear**	Not required

Product Loading

Facing	330 ml can	28	600 ml bottle	28
Loading	330 ml can	168	600 ml bottle	168

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)	
Maximum Ambient Temperature (°C)	40	
Sound Level (dB(A))	Standard	< 66
	Hush Mode*	< 62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	9
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	2.1 kWh/24 h
Annual Running Costs	$230 (@ $0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9 power cord with 3-pin, 10 amp plug
Current draw (A)	2.6

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)			
System Type	Removable cartridge			
Cartridge Weight (kg)	24			
Refrigerant/Charge	R290/81 g			
Nominal Capacity (W)	650			
Heat Rejection (W)	Average	90	Peak	110
Defrost Type	Automatic, off-cycle			
Drainage	No plumbing required			

* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

BB.2.GSW
on the SKOPE website

© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.

Email: skope@skope.com AUS Freephone: 1800 121 535 NZ Freephone: 0800 947 5673

skope.com