PHOENIX

Fast Food Equipment
Bakery Equipment



Shanghai Phoenix Industrial Co.,Ltd

FAST FOOD EQUIPMENT

Chicken Pressure Fryer

PHOENIX



PFE-800/PFG-800



PFE-600/PFG-600



PFE-600L/PFG-600L



PFE-500/PFG-500

Electric Pressure Fryers

- All models with built-in filtration system

Model	Power	Voltage	Capacity	Dimension	Net weight	Control Panel
PFE-800	13.5kW	3N~380V/50Hz	24L	460×960×1230mm	135kg	Computer Panel
PFE-600	13.5kW	3N~380V/50Hz	24L	460×960×1230mm	135kg	Computer Panel
PFE-600L	13.5kW	3N~380V/50Hz	24L	460×960×1230mm	135kg	LCD Panel
PFE-500	13.5kW	3N~380V/50Hz	24L	460×960×1230mm	135kg	Mechanical Panel

Gas Pressure Fryers

- All models with built-in filtration system

Model	Gas Consume	Voltage	Capacity	Dimension	Net weight	Control Panel
PFG-800	0.55kW	220V/50Hz	25L	460×960×1230mm	135kg	Computer Panel
PFG-600	0.55kW	220V/50Hz	25L	460×960×1230mm	135kg	Computer Panel
PFG-600L	0.55kW	220V/50Hz	25L	460×960×1230mm	135kg	LCD Panel
PFG-500	0.55kW	220V/50Hz	25L	460×960×1230mm	135kg	Mechanical Panel

FAST FOOD EQUIPMENT

Chicken Pressure Fryer

PHOENIX



Features

- Built-in filtration system reduces downtime and increases employees' productivity
- 10 programmable cook cycle.(for Model PFE-600 & PFE-800)
- Programmable control, LED time/temp display and simple up/down arrows
- Heavy-duty stainless steel rectangular fry pot for easy-cleaning and long life
- Larger 6-head capacity fry pot
- High-efficiency heating elements generate fast temperature recovery and energy savings
- Cast aluminum alloy lid is strong but light for easy handling
- Color-keyed locking spindle engages pressure seal
- Lid-lock system keeps lid locked until pressure reaches 1 psi
- Raised edge on deck reduces spills
- Channel under lid helps direct condensation away from pot when lid is open
- High-limit temperature protection
- 4 heavy duty casters, 2 locking





MDXZ-16

Electric Counter-top Pressure Fryer

Voltage:220V～240V/50Hz
Power:3kW
Temperature ragnge: 20～200℃
Capacity:16L
Dimension: 380×470×530mm
Net weight: 19kg



Frying Pot Capacity 16L



Basket Inside



Oil Level Mark



whole stainless steel body



MDXZ-24

Electric Pressure Fryer

Voltage:3N～380V/50Hz
Power:13.5kW
Capacity:24L
Dimension: 460×960×1230mm
Net weight: 110kg
Control Panel: Mechanical Panel



MDXZ-25

Gas Pressure Fryer

Voltage:220V/50Hz
Capacity:25L
Dimension: 460×960×1230mm
Net weight: 110kg
Control Panel: Mechanical Panel



OFE-321/OFG321



OFE-322/OFG-322



OFE-323/OFG-323

Electric Open Fryer

Model	Power	Voltage	Capacity	Dimension	Temperature range	Net weight	Gross weight
OFE-321	14.2kW	3N~380V/50Hz	25L	441×949×1180mm	20~190℃	128kg	148kg
OFE-322	27.7kW	3N~380V/50Hz	2×25L	882×949×1180mm	20~190℃	185kg	208kg
OFE-323	41.2kW	3N~380V/50Hz	3×25L	1323×949×1180mm	20~190℃	237kg	260kg

Gas Open Fryer

Model	Power	Voltage	Capacity	Dimension	Temperature range	Net weight	Gross weight
OFG-321	LPG or Natural Gas	220V/50Hz	25L	440×900×1130mm	20~190℃	138kg	158kg
OFG-322	LPG or Natural Gas	220V/50Hz	2×25L	850×900×1130mm	20~190℃	212kg	234kg
OFG-323	LPG or Natural Gas	220V/50Hz	3×25L	1250×900×1130mm	20~190℃	279kg	301kg



OFE-321L/OFG-321L



OFE-322L/OFG-322L



OFE-323L/OFG-323L

Electric Open Fryer

Model	Power	Voltage	Capacity	Dimension	Temperature range	Net weight	Gross weight
OFE-321L	14.2kW	3N~380V/50Hz	25L	441×949×1180mm	20~190℃	128kg	148kg
OFE-322L	27.7kW	3N~380V/50Hz	2×25L	882×949×1180mm	20~190℃	185kg	208kg
OFE-323L	41.2kW	3N~380V/50Hz	3×25L	1323×949×1180mm	20~190℃	237kg	260kg

Gas Open Fryer

Model	Power	Voltage	Capacity	Dimension	Temperature range	Net weight	Gross weight
OFG-321L	LPG or Natural Gas	220V/50Hz	25L	440×900×1130mm	20~190℃	138kg	158kg
OFG-322L	LPG or Natural Gas	220V/50Hz	2×25L	850×900×1130mm	20~190℃	212kg	234kg
OFG-323L	LPG or Natural Gas	220V/50Hz	3×25L	1250×900×1130mm	20~190℃	279kg	301kg



OFE-22A

Voltage:3N～380V/50Hz
Power:18.5kW
Temperature ragnge: 20～190℃
Capacity:22L
Dimension: 900×445×1210mm
Gross weight:125kg



OFE-28A

Voltage:3N～380V/50Hz
Power:2×8.5kW
Temperature ragnge: 20～190℃
Capacity:2×13L
Dimension: 515×890×1015mm
Gross weight:125kg



OFE-42A

Voltage:3N～380V/50Hz
Power:8.5+17kW
Temperature ragnge: 20～190℃
Capacity:13+26L
Dimension: 700×940×1180mm
Gross weight:140kg



OFE-56A

Voltage:3N～380V/50Hz
Power:4×8.5kW
Temperature ragnge: 20～190℃
Capacity:4×13L
Dimension: 1020×860×1015mm
Net weight: 156kg
Gross weight: 180kg



OFE-H321L



OFE-H321

Electric Open Fryer

Model	Power	Voltage	Capacity	Dimension	Temperature range	Net weight
OFE-H321L	13.5kW	3N～380V/50Hz	25L	440×890×1150mm	20～190℃	110kg
OFE-H321	13.5kW	3N～380V/50Hz	25L	450×940×1190mm	20～190℃	130kg



OFE-H28A



OFE-H56A

Electric Automatically Lift Open Fryer

Model	Power	Voltage	Capacity	Dimension	Temperature range	Net weight
OFE-H28A	17kW	3N～380V/50Hz	2×13L	440×890×1150mm	20～190℃	110kg
OFE-H56A	4×8.5kW	3N～380V/50Hz	4×13L	930×860×1200mm	20～190℃	170kg



Vacuum Marinated Machine

Model:YA-809

Voltage:220V～240V/50Hz
Power:0.18+0.17kW
Mixing Speed: 32r/min
Size:953×860×914mm
Packing:1000×885×975mm
Net weight: 65kg



Marinated Machine

Model:YA-900

Voltage:220V～240V/50Hz
Power:0.18kW
Mixing Speed: 32r/min
Size:953×660×914mm
Packing:1000×685×975mm
Net weight: 59kg



Warming Showcase

Model:DBG-1500

Voltage: 3N～380V 50-60Hz
Power: 3.5kW
Temperature:50～90℃
Size: 1520×790×950mm



Electric Chicken Breader

Model:GW-2400

Voltage:3N～380V/50Hz
Power:0.4kW
Heating Method: Electric
Size: 1200×700×950mm



Center Island

VCI-120

Size: 1200×760×780mm

Material: Stainless Steel



Chips Warmer

VF-98

Voltage: 220V/50Hz

Power: 1.1kW

Size: 1000×700×1500mm



Vertical Warming Showcase

HHC-903

Voltage: 220V/50Hz

Power: 2.5kW

Temperature range: 20～100℃

Size: 630×800×1010mm



Vertical Warming Showcase

HHC-980

Voltage: 220V/50Hz

Power: 2.5kW

Temperature: 20～100℃

Size: 630×800×1760mm

BAKERY EQUIPMENT

Rotary Oven 32 trays

PHOENIX



YZD-100/YKZ-100/YKG-100
YZD-100AD/YKZ-100AD/YKG-100AD



YZD-100BD/YKZ-100BD/YKG-100BD

Parameter

Product name	Electric Rotary Oven	Diesel Oil Rotary Oven	Gas Rotary Oven
Model	YZD-100 YZD-100AD/YZD-100BD	YKZ-100 YKZ-100AD/YKZ-100BD	YKG-100 YKG-100AD/YKG-100BD
Voltage	3～380V/50Hz	3～380V/50Hz	3～380V/50Hz
Power	52kW	3kW	3kW
Temperature ragnge	20～300℃	20～300℃	20～300℃
Productivity	100kg/h	100kg/h	100kg/h
Gas Consumption		2.5-3kg/h	1.2～2.3m³/h9(LPG)
Trolley Size	610×810×1730mm	610×810×1730mm	610×810×1730mm
Trays Size	400×600mm	400×600mm	400×600mm
Overall Dimension	1900×1800×2300mm 2050×2000×2150mm	1900×1800×2300mm 2050×2000×2150mm	1900×1800×2300mm 2050×2000×2150mm
Net weight	1300kg/1350kg	1300kg/1350kg	1300kg/1350kg

BAKERY EQUIPMENT

Deck Oven



YXD-F30A



YXD-F30A

Parameter

Model	Power	Voltage	Tray Qty	Tray Size	Temperature range	Dimension
YXD-F30A	6.8kW	3N～380V/50Hz	1 layers 2 plates	400×600mm	0～300℃	1240×920×400mm
YFD-F60A	13.6kW	3N～380V/50Hz	2 layers 4 plates	400×600mm	0～300℃	1240×920×1230mm



YXD-F30A



YXD-F120A



YXD-F9A

Parameter

Model	Power	Voltage	Tray Qty	Tray Size	Temperature range	Dimension
YFD-F90A	20.4kW	3N～380V/50Hz	3 layers 6 plates	400×600mm	0～300℃	1240×920×1630mm
YXD-F120A	27.2kW	3N～380V/50Hz	4 layers 8 plates	400×600mm	0～300℃	1240×920×2190mm
YFD-F9A	4×2.8kW	220V/50Hz	4 layers 4 plates	400×600mm	0～300℃	785×950×1520mm



Convection Oven

YKZ-5A
Voltage:3N～380V
Power: 9kW
Tray Size: 400×600mm

YXD-F30A
Voltage:3N～380V
Power: 6.8kW
Tray Size: 400×600mm

YXD-F30A
Voltage:220V
Power: 5kW
Tray Size: 400×600mm

Water Chiller

YXD-800A

Voltage:3N～380V

Frequency: 50/60Hz

Power:13kw (upper layer 7kw+middle layer 4kw+lower layer 2kw)

Oven temperature: 0~300℃

Alarm temperature: 0~50℃

Volume:1345mm*820mm*1970mm

Weight:290kg



YXD-800A

Planetary Mixer



B-20/B-30/B-40/B-50



B-60

B-20

Voltage: 220V/50Hz
Power: 1.1kW/h
Capacity: 20L
Mixing Speed: 100/180/400r/min
Productivity: 2-3kg
Dimension: 490×420×780mm
Net Weight: 90kg

B-30

Voltage: 220V/50Hz
Power: 1.5kW/h
Capacity: 30L
Mixing Speed: 110/200/420r/min
Productivity: 3-6kg
Dimension: 520×430×890mm
Net Weight: 103kg

B-40

Voltage: 3N~380V/50Hz
Power: 2kW/h
Capacity: 40L
Mixing Speed: 65/102/296r/min
Productivity: 6-8kg
Dimension: 550×650×1060mm
Net Weight: 150kg

B-50

Voltage: 3N~380V/50Hz
Power: 2.2kW
Capacity: 50L
Mixing Speed: 74/141/277r/min
Productivity: 5-9kg
Dimension: 610×650×1350mm
Net Weight: 385kg

B-60

Voltage: 3N~380V/50Hz
Power: 3kW
Capacity: 60L
Mixing Speed: 74/141/277r/min
Productivity: 6-10kg
Dimension: 610×650×1360mm
Net Weight: 420kg

BAKERY EQUIPMENT

PHOENIX



ZT-36



BKD-16/BKD-20



FC-2-30



FC-3-30

Dough Divider

Model	Power	Voltage	Pieces	Overall Size	Weight of each pice	Net weight
ZT-36	1.1kW	220V/50Hz	36	440×500×1300mm	30～180g	180kg

Hydraulic Dough Divider

Model	Division	Weight Range	Dough Weight	Power	Dimension	Voltage	Net weight
BKD-16	16pcs	125-1000g	16kg	1.5kW	620×810×1100mm	3N～380/220～50Hz	350kg
BKD-20	20pcs	100-800g	16kg	1.5kW	620×810×1100mm	3N～380/220～50Hz	350kg

Full Automatic Dough Divider And Rounder

Model	Power	Voltage	Yield	Single Grain Weight	Overall Size	Packaing Size	Packing Weight	Net Weight
FC-2-30	1.5kW	3N～380V	30 capsules/time	30 g/grain	700×720×1500mm	750×750×1600mm	420kg	400kg

Semi Automatic Dough Divider And Rounder

Model	Power	Voltage	Pieces	Weight of each piece	Overall Size	Cable	Net Weight
FC-2-30	0.75kW	3N～380V/50Hz	30	30 -100g	640×540×2100mm	4c*1.5	180kg

Dough Mixer



ZZ-240



ZZ-120



ZZ-40,60,80

Parameter

Model	ZZ-240	ZZ-120	ZZ-80	ZZ-60	ZZ-40
Power	4/7.5kW	3/4.5kW	2.2/3.3kW	1.5/2.4kW	0.85/1.1kW
Voltage	3N～380V/50Hz	3N～380V/50Hz	3N～380V/50Hz	3N～380V/50Hz	3N～380V/50Hz
Capacity	240L	122L	88L	68L	48L
Productivity	100kg powder	50kg powder	35kg powder	25kg powder	16kg powder
Mixing Speed	125/250r/min	125/250r/min	125/250r/min	115/230r/min	114/230r/min
Bowl Speed	10/20r/min	10/20r/min	10/20r/min	10/20r/min	12/24r/min
Bowl Thickness	3.5mm	3.5mm	2.5mm	2.5mm	2.0mm
Panel	computer panel	computer panel	mechanical	mechanical	mechanical

Bread Slicer

HLM-31

Voltage: 220V/50Hz

Power: 0.25kW

Pieces: 30 pieces

Overall Size: 680×780×780mm

Slice Width: 12mm

Net Weight: 52kg



HLM-31



F750

Baguette Moulder

F750

Voltage: 220V～380V/50Hz

Power: 0.75kW

Dough Range: 50-1200g

Overall Size: 980×700×1430mm

Net Weight: 285kg

Pizz Dough Pressing Machine

	PIZ-235	PIZ-235A
Voltage	220V	220V
Power	400kW	400kW
Motor Speed	400r/min	400r/min
Overall Size	595×560×650mm	560×560×500mm
Net Weight	83kg	63kg



PIZ-235/PIZ-235A



CG-38

Toast Moulder

CG-300

Voltage:220V/50Hz

Regeneration: 0.75kW

Hours: 2000 pieces

Overall Size: 500×1050×1300mm

Net Weight: 193kg

Caterpillar Pizza Oven

YXP-500

Voltage:3N～380V/50Hz

Power: 13kW

Speed: 3～12min/r

Temperature Range: 0～300℃

Size: 1810×1200×1070mm



YXP-500



SP-500

Dough Sheeter

SP-500

Voltage:3N～380V/50Hz

Motor Power: 0.55kW

Rated Power: 0.75kW

Water Proof Grade: 1P×1mm

Axis Width: 520mm

Overall Size: 2430×880×1230mm

Package Size: 1000×760×1680mm

Net Weight: 280kg

BAKERY EQUIPMENT

PHOENIX



YKZ-12/YKG-12

12 trays Convection Oven

Model	YKZ-12	YKG-12
Energy	electric	LPG
Voltage	3N～380V/50Hz	3N～380V/50Hz
Power	19.8kW	0.75kW
Productivity	45kg/h	45kg/h
Temp.Range	20～300℃	20～300℃
Tray Size	400×600mm	400×600mm
Net weight	300kg	300kg
Dimension	1000×1530×1845mm	1000×1530×1845mm

5 trays Convection Oven and 10 trays prover

Model	YKZ-5D	FX-10
Productivity	20kg/h	
Voltage	3N～380V/50Hz	220V/50Hz
Power	9kW	2.4kW/h
Temp.Range	20～300℃	20～100℃
Tray Size	400×600mm	
Net weight	130kg	50kg
Dimension	900×1170×730mm	900×1170×680mm



YKZ-5D/FX-10



Single Door Chilling Prover

YXF-32RS

Voltage:220V
Regeneration: 0.75kW
Proofing: 2kW
Temperature Range: -28～50℃
Dimension: 790×1350×1980mm

Prover Series



YXZ-32

Voltage:220V/50Hz
Power:6.0kW/h
Trolley: one
Temperature Range:20～60℃
Dimension: 910×1360×2050mm



YXZ-64

Voltage:220V/50Hz
Power:6.0kW/h
Trolley: two
Temperature Range:20～60℃
Dimension: 1740×1360×2050mm

SHANGHAI PHOENIX INDUSTRIAL CO., LTD

Address : No.1525 Minqiang Road, SongJiang District, Shanghai,China

Tel.: +86 21 33555038

Mobile: +86 18616995800

Email: phoenixchina@outlook.com

Web: www.phoenixindustry.cn