# **THERMOWELL** TECHNICAL DATASHEET



| | TW4 | | TW9 | | TW15 | | TW18 | |
|---|---|---|---|---|---|---|---|---|
| Dimensions (mm) | External | Internal | External | Internal | External | Internal | External | Internal |
| Width | 638 | 345 | 980 | 687 | 1510 | 1217 | 1862 | 1569 |
| Depth | 385 | 305 | 385 | 305 | 385 | 305 | 385 | 305 |
| Depth (Lid Open) | 447 | - | 447 | - | 447 | - | 447 | - |
| Height | 241 | 105 | 241 | 105 | 241 | 105 | 241 | 105 |
| Height (Lid Open) | 563 | - | 563 | - | 563 | - | 563 | - |
| Capacity | | | | | | | | |
| Capacity 1/3 GN Containers | | 2 | | 4 | | 7 | | 9 |

## KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Designed to accommodate 2,4,7 or 9 x 1/3 pans depending on model
- Digital thermometer and adjustable thermostat
- Designed and engineered to operate efficiently up to a 32°C ambient
- Hinged lid designed to stay open
- Precision injected, high density polyurethane insulation
- Fitted with rubber feet
- Removable unit cover
- Accepts 100mm deep 1/6GN and 1/3GN pans

## OPTIONS

- Wall mounting kit
- Counter mounting kit
- Free standing extended legs (350mm incl. feet)
- Bridging bars
- 1/6 Stainless steel gastronorm pans
- 1/3 Stainless steel gastronorm pans

www.williams-refrigeration.co.uk

# **THERMOWELLS** TECHNICAL DATA

| Thermowell | TW4 | TW9 | TW15 | TW18 |
|---|---|---|---|---|
| Temperature (°C) | +4/+8 | +4/+8 | +4/+8 | +4/+8 |
| Power Supply | | 220V/240V/50/Hz/1Ph | | |
| Fuse (Amps) | 13 | 13 | 13 | 13 |
| Noise Level (dBA) | 40.0 | 40.0 | 42.0 | 42.0 |

| Fittings | |
|---|---|
| GN Pans | Can accept 1/3, 1/6GN pans not included |

| Electrical Data - Standard Refrigerant | | | | |
|---|---|---|---|---|
| Refrigerant | R134a | R134a | R134a | R134a |
| Energy Consumption (kW / 24hrs)* | 1.1 | 1.36 | 1.53 | 1.8 |
| Start Up (Amps) | 8.35 | 8.35 | 8.35 | 8.35 |
| Running (Amps) | 1.25 | 1.25 | 1.25 | 1.25 |
| Heat Rejection (kW / 24hrs)** | 267 | 267 | 267 | 267 |

**IMPORTANT NOTES:**

**Energy consumption is tested to EN153 in 24hrs

***Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk